

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.08.2022

Version number 15 (replaces version 14)

Revision: 29.08.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- Trade name: **COELASTIC EVO light gray**
- UFI: VKD8-90KV-800R-F2Q9
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Application of the substance / the mixture Identified use: intended for professional use only!
Waterproofing
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier: KEMPER SYSTEM LTD
Kemper House
30 Kingsland Grange
Warrington
WA1 4RW
www.kempersystem.co.uk
enquiries@kempersystem.co.uk
phone: +44 (0)1925 445532
fax: +44 (0)1925 575096
- Further information obtainable from: research & development
- 1.4 Emergency telephone number: Medical Emergency information in case of poisoning:
Poison Information Center Mainz - 24 h - Phone: +49 (0) 6131 19240
(advisory service in German or English language)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008
Flam. Liq. 3 H226 Flammable liquid and vapour.
Eye Irrit. 2 H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.
- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
- Hazard pictograms
- The product is classified and labelled according to the GB CLP regulation.
- 

- GHS02 GHS07
- Signal word
- Warning
- Hazard-determining components of labelling:
- Poly[oxy(methyl-1,2-ethanediyl)], alpha-hydro-omega-hydroxy-, polymer with 2,4-diisocyanato-1-methylbenzene
1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate
Isophorondiisocyanate homopolymer
Phenol, methylstyrenated
m-tolyldiene diisocyanate
trimethoxyvinylsilane
- Hazard statements
- H226 Flammable liquid and vapour.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.
- Precautionary statements
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- Additional information:
- EUH204 Contains isocyanates. May produce an allergic reaction.
EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.08.2022

Version number 15 (replaces version 14)

Revision: 29.08.2022

Trade name: **COELASTIC EVO light gray**

(Contd. of page 1)

- vPvB: Not applicable.

- Determination of endocrine-disrupting properties

68512-30-1 | Phenol, methylstyrenated

List II

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures

- Description: Mixture: consisting of the following components.

- Dangerous components:

CAS: 37273-56-6 EC number: 609-378-7	Poly[oxy(methyl-1,2-ethanediyl)], alpha-hydro-omega-hydroxy-, polymer with 2,4-diisocyanato-1-methylbenzene Eye Irrit. 2, H319; Skin Sens. 1, H317	25-50%
CAS: 7727-43-7 EINECS: 231-784-4 Reg.nr.: 01-2119491274-35	barium sulphate, natural substance with a Community workplace exposure limit	12.5-25%
CAS: 64742-95-6 EINECS: 265-199-0 Index number: 649-356-00-4 Reg.nr.: 01-2119455851-35	Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336, EUH066	10-12.5%
CAS: 140921-24-0 ELINCS: 411-700-4 Index number: 616-079-00-5 Reg.nr.: 01-2119890830-32	1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate Skin Sens. 1, H317	2.5-10%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17	titanium dioxide Carc. 2, H351	0.5-2.5%
CAS: 53880-05-0 EC number: 931-312-3 Reg.nr.: 01-2119488734-24	Isophorondiisocyanate homopolymer Skin Sens. 1, H317; STOT SE 3, H335	≥1-<2.5%
CAS: 68512-30-1 EINECS: 270-966-8 Reg.nr.: 01-2119555274-38	Phenol, methylstyrenated Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.5-<1%
CAS: 2768-02-7 EINECS: 220-449-8 Reg.nr.: 01-2119513215-52	trimethoxyvinylsilane Flam. Liq. 3, H226; Acute Tox. 4, H332; Skin Sens. 1B, H317	≥0.1-<0.5%
CAS: 26471-62-5 EINECS: 247-722-4 Index number: 615-006-00-4 Reg.nr.: 01-2119454791-34	m-tolylidene diisocyanate Acute Tox. 2, H330; Resp. Sens. 1, H334; Carc. 2, H351; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412, EUH204 Specific concentration limit: Resp. Sens. 1; H334: C ≥ 0.1 %	<0.1%
CAS: 4098-71-9 EINECS: 223-861-6 Index number: 615-008-00-5 Reg.nr.: 01-2119490408-31	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate Acute Tox. 1, H330; Resp. Sens. 1, H334; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Resp. Sens. 1; H334: C ≥ 0.5 % Skin Sens. 1; H317: C ≥ 0.5 %	<0.1%

- Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures

- General information:

Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
Do not leave affected persons unattended.
Personal protection for the First Aider.
Take affected persons out of danger area and lay down.

- After inhalation:

In case of unconsciousness place patient stably in side position for transportation.
Supply fresh air; consult doctor in case of complaints.

- After skin contact:

Immediately wash with water and soap and rinse thoroughly.
Seek medical treatment in case of complaints.

- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
Protect unharmed eye.

- After swallowing:

If symptoms persist consult doctor.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.08.2022

Version number 15 (replaces version 14)

Revision: 29.08.2022

Trade name: **COELASTIC EVO light gray**

(Contd. of page 2)

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire extinguishing methods suitable to surrounding conditions.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
 - Hydrogen cyanide (HCN)
 - Formation of toxic gases is possible during heating or in case of fire.
 - Nitrogen oxides (NO_x)
 - Carbon monoxide (CO)
- **5.3 Advice for firefighters**
- **Protective equipment:** Do not inhale explosion gases or combustion gases.
- **Additional information** Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation. Keep away from ignition sources. Avoid contact with skin and eyes.
- **6.2 Environmental precautions:** Inform respective authorities in case of seepage into water course or sewage system. Prevent from spreading (e.g. by damming-in or oil barriers). Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Do not flush with water or aqueous cleansing agents. See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.
- **6.4 Reference to other sections**

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Store in cool, dry place in tightly closed receptacles. Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- **Information about fire - and explosion protection:** Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**
 - Protect from frost.
 - Store in dry conditions.
 - Keep container tightly sealed.
 - Recommended storage temperature: 5-30 °C
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

GB
(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.08.2022

Version number 15 (replaces version 14)

Revision: 29.08.2022

Trade name: **COELASTIC EVO light gray**

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters

- Ingredients with limit values that require monitoring at the workplace:

7727-43-7 barium sulphate, natural

WEL	Long-term value: 10* 4** mg/m ³ *inhalable dust **respirable dust
-----	---

26471-62-5 m-tolylidene diisocyanate

WEL	Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO
-----	---

4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

WEL	Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO
-----	---

- Regulatory information WEL: EH40/2020

- DNELs

7727-43-7 barium sulphate, natural

Inhalative	Acute - systemic effects	10 mg/m ³ (Worker) (GESTIS DNEL List (June 2018))
------------	--------------------------	--

- Ingredients with biological limit values:

4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

BMGV	1 µmol creatinine/mol Medium: urine Sampling time: At the end of the period od exposure Parameter: isocyanate-derived diamine
------	--

- Additional information: The lists valid during the making were used as basis.

- 8.2 Exposure controls

- Appropriate engineering controls

No further data; see item 7.

- Individual protection measures, such as personal protective equipment

- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

- Respiratory protection:

When used properly and under normal conditions, breathing protection is not required.
Use suitable respiratory protective device in case of insufficient ventilation.
Filter A/P2

- Hand protection

Respiratory protection - Gas filters and combination filters according to (DIN EN 141)



Protective gloves

Only use chemical-protective gloves with CE-labelling of category III.
Check protective gloves prior to each use for their proper condition.
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
After use of gloves apply skin-cleaning agents and skin cosmetics.

- Material of gloves

Recommended materials:

Butyl rubber, BR
Recommended thickness of the material: ≥ 0.5 mm
Penetration time (min.): < 480

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

- Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

- As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR
Recommended thickness of the material: ≥ 0.1 mm
Penetration time (min.): < 10

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.08.2022

Version number 15 (replaces version 14)

Revision: 29.08.2022

Trade name: **COELASTIC EVO light gray**

- Eye/face protection



Tightly sealed goggles

(Contd. of page 4)

- Body protection:

Protective goggles and facial protection - Classification according to EN 166 protective clothing (EN 13034)

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties

- General Information

- Colour:	According to product specification
- Odour:	Aromatic
- Odour threshold:	Not determined.
- Melting point/freezing point:	Undetermined.
- Boiling point or initial boiling point and boiling range	Undetermined.
- Flammability	Not applicable.
- Lower and upper explosion limit	
- Lower:	Not determined.
- Upper:	Not determined.
- Flash point:	31 °C
- Decomposition temperature:	Not determined.
- pH	Not determined.
- Viscosity:	
- Kinematic viscosity at 20 °C	119 s (ISO 6 mm)
- Dynamic:	Not determined.
- Solubility	
- water:	Not miscible or difficult to mix.
- Partition coefficient n-octanol/water (log value)	Not determined.
- Density and/or relative density	
- Density at 20 °C:	1.45 g/cm ³
- Relative density	Not determined.
- Vapour density	Not determined.

- 9.2 Other information

- Appearance:	
- Form:	Fluid
- Important information on protection of health and environment, and on safety.	
- Auto-ignition temperature:	Product is not selfigniting.
- Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- Solvent separation test:	
- VOC (EC)	15.88 %
- Change in condition	
- Evaporation rate	Not determined.

- Information with regard to physical hazard classes

- Explosives	Void
- Flammable gases	Void
- Aerosols	Void
- Oxidising gases	Void
- Gases under pressure	Void
- Flammable liquids	Flammable liquid and vapour.
- Flammable solids	Void

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.08.2022

Version number 15 (replaces version 14)

Revision: 29.08.2022

Trade name: **COELASTIC EVO light gray**

(Contd. of page 5)

- Self-reactive substances and mixtures

Void

- Pyrophoric liquids

Void

- Pyrophoric solids

Void

- Self-heating substances and mixtures

Void

- Substances and mixtures, which emit flammable gases in contact with water

Void

- Oxidising liquids

Void

- Oxidising solids

Void

- Organic peroxides

Void

- Corrosive to metals

Void

- Desensitised explosives

Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions Reacts with alcohols, amines, aqueous acids and alkalis.
Reacts with water.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: Amines, acids, alkalis, strong oxidants, alcohols
- 10.6 Hazardous decomposition products: Hydrogen chloride (HCl)
Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.

- LD/LC50 values relevant for classification:

37273-56-6 Poly[oxy(methyl-1,2-ethanediyl)], alpha-hydro-omega-hydroxy-, polymer with 2,4-diisocyanato-1-methylbenzene

Oral	LD50	>5,000 mg/kg (rat)
------	------	--------------------

7727-43-7 barium sulphate, natural

Oral	LD50	>15,000 mg/kg (rat)
------	------	---------------------

Dermal	LD50	>2,000 mg/kg (rat)
--------	------	--------------------

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>5,000 mg/kg (rat)
------	------	--------------------

Dermal	LD50	>3,160 mg/kg (rabbit) (OECD 402)
--------	------	----------------------------------

140921-24-0 1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate

Oral	LD50	>5,000 mg/kg (rat)
------	------	--------------------

Dermal	LD50	>2,000 mg/kg (rat)
--------	------	--------------------

53880-05-0 Isophorondiisocyanate homopolymer

Oral	LD50	>14,000 mg/kg (rat) (OECD 401)
------	------	--------------------------------

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.08.2022

Version number 15 (replaces version 14)

Revision: 29.08.2022

Trade name: **COELASTIC EVO light gray**

(Contd. of page 6)

68512-30-1 Phenol, methylstyrenated

Oral	LD50	>2,000 mg/kg (rat) (OECD 423)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)

2768-02-7 trimethoxyvinylsilane

Oral	LD50	7,340-7,460 mg/kg (rat) (OECD 401)
Dermal	LD50	3,460-4,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/4 h	16.79 mg/l (rat)

26471-62-5 m-tolylidene diisocyanate

Oral	LD50	5,110 mg/kg (rat)
Inhalative	LC50/4 h	0.107 mg/l (rat)
	LC50/1 h	0.47 mg/l (rat)

4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

Inhalative	LC50/4 h	0.05 mg/l (ATE)
------------	----------	-----------------

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

- Endocrine disrupting properties

68512-30-1 | Phenol, methylstyrenated

List II

SECTION 12: Ecological information**- 12.1 Toxicity****- Aquatic toxicity:****37273-56-6 Poly[oxy(methyl-1,2-ethanediyl)], alpha-hydro-omega-hydroxy-, polymer with 2,4-diisocyanato-1-methylbenzene**

EC50	>10,000 mg/l (Belebtschlamm) (OECD 209)
------	---

7727-43-7 barium sulphate, natural

EC50	32 mg/l (Daphnia magna) (Ba-Ion; 48 h)
------	--

64742-95-6 Solvent naphtha (petroleum), light arom.

LL 50	9.2 mg/l (fish) (96h; OECD 203)
EC50	3.2 mg/l (Daphnia magna) (48h; OECD 202)
EC50	2.6 mg/l (Pseudokirchneriella subcapitata) (72h; OECD 201)

140921-24-0 1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate

LC50/96 h	316 mg/l (Danio rerio (Zebraabärling)) (OECD 203)
EC50	1.77 mg/l (Bakterien) (activated sludge; ISO 8192-1986 E)
IC50	43 mg/l (DESMODESMUS SUBSPICATUS) (72h; OECD 201)
EC50	193 mg/l (Daphnia magna) (48h; OECD 202)

53880-05-0 Isophorondiisocyanate homopolymer

LC50/96 h	>1.51 mg/l (Cyprinus Carpio) (Richtlinie 67/548/EWG, Anhang V, C.1.)
EC50	>3.36 mg/l (Daphnia magna) (OECD 202)
EC50	>10,000 mg/l (Belebtschlamm) (OECD 209)

68512-30-1 Phenol, methylstyrenated

ErC50	15 mg/l (daphnia) (OECD TG 201)
LC50/96 h	25.8 mg/l (daphnia) (OECD TG 203)
EC50	14-51 mg/l (daphnia) (OECD TG 202)

2768-02-7 trimethoxyvinylsilane

NOEC	28 mg/kg (Daphnia magna) (21d)
EC50	>100 mg/l (Daphnia magna) (OECD 202)
EC50	297.2 mg/l (Daphnia magna) (24h)
EC10	1.1 mg/l (Pseudomonas putida) (3h; acute)

(Contd. on page 8)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.08.2022

Version number 15 (replaces version 14)

Revision: 29.08.2022

Trade name: COELASTIC EVO light gray

(Contd. of page 7)

EC50	32 mg/l (Selenastrum capricornutum) (7d; acute) >100 mg/l (DESMODESMUS SUBSPICATUS) (72h; Growth Inhibition Test; acute) >100 mg/l (daphnia) (48h; Watery twigs acute) 168.7 mg/l (Daphnia magna) (48h)
EC50	210 mg/l (Selenastrum capricornutum) (7d; static acute)
LC 50	191 mg/l (Oncorhynchus mykiss (Regenbogenforelle)) (96h acute)
LC50	>100 mg/l (Brachydanio rerio (Ricefish)) (96h; static acute)
NOEC	28 mg/l (Daphnia magna) (21d)
NOEC	25 mg/l (Selenastrum capricornutum) (7d; acute)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:** Harmful to aquatic organisms
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Disposal according to official regulations

- **European waste catalogue**

08 05 01*	waste isocyanates
15 01 10*	packaging containing residues of or contaminated by hazardous substances
17 02 03	plastic

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG** Void
- **IATA** UN1866

- **14.2 UN proper shipping name**
- **ADR, IMDG** Void
- **IATA** RESIN SOLUTION

- **14.3 Transport hazard class(es)**
- **ADR, ADN, IMDG**
- **Class** Void
- **IATA**



- **Class** 3 Flammable liquids.
- **Label** 3

- **14.4 Packing group**
- **ADR, IMDG** Void
- **IATA** III

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.08.2022

Version number 15 (replaces version 14)

Revision: 29.08.2022

Trade name: **COELASTIC EVO light gray**

(Contd. of page 8)

- 14.5 Environmental hazards:	
- Marine pollutant:	No
- 14.6 Special precautions for user	Not applicable.
- 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
- Transport/Additional information:	
- ADR	
- Remarks:	Kein Gut der Kl. 3 gemäß 2.2.3.1.5 ADR / 2.3.2.5 IMDG-Code ADR / IMDG: Verpackung > 450 l = UN 1866 - Kl. 3 - HARZLÖSUNG, entzündbar - VPIII Außerhalb ADR / IMDG = UN 1866 - Kl. 3 - HARZLÖSUNG, entzündbar - VPIII Not goods of cl. 3 in accordance with 2.2.3.1.5 ADR / 2.3.2.5 IMDG-Code ADR / IMDG: Packaging > 450 l = UN 1866 - cl. 3 - RESIN SOLUTION, flammable - PGIII Outside ADR / IMDG = UN 1866 - cl. 3 - RESIN SOLUTION, flammable - PGIII
- UN "Model Regulation":	Void

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU

- Named dangerous substances - ANNEX I None of the ingredients is listed.

- Seveso category P5c FLAMMABLE LIQUIDS

- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 74

- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- REGULATION (EU) 2019/1148

- Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

- Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

- Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

- Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The safety data sheet issued is also compliant with the regulation Annex I of Regulation (EU) no. 453/2010 and Annex II of Regulation (EU) no. 2020/878.

- Relevant phrases	H226 Flammable liquid and vapour.
	H304 May be fatal if swallowed and enters airways.
	H315 Causes skin irritation.
	H317 May cause an allergic skin reaction.
	H319 Causes serious eye irritation.
	H330 Fatal if inhaled.
	H332 Harmful if inhaled.
	H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
	H335 May cause respiratory irritation.
	H336 May cause drowsiness or dizziness.
	H351 Suspected of causing cancer.
	H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.08.2022

Version number 15 (replaces version 14)

Revision: 29.08.2022

Trade name: COELASTIC EVO light gray

(Contd. of page 9)

H412 Harmful to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.
EUH204 Contains isocyanates. May produce an allergic reaction.

- Department issuing SDS:
- Contact:
- Date of previous version:
- Version number of previous version:
- Abbreviations and acronyms:

research & development
research & development
13.06.2022
14

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 1: Acute toxicity – Category 1
Acute Tox. 2: Acute toxicity – Category 2
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1B: Skin sensitisation – Category 1B
Carc. 2: Carcinogenicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

- **Sources**

- www.echa.europa.eu
- www.baua.de

IFA: Institute für Occupational Safety and Health of the German Social Accident Insurance:
- www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index.jsp
- www.dguv.de/ifa/gestis/gestis-dnel-liste

- * Data compared to the previous version altered.